

RUGGED CONSTRUCTION

SUPERIOR DESIGN IN TRUCK BODY FABRICATION











PB9600 Standard Platform / Stake Bodies

Standard Specifications & Options

- 42" or 48" high weld-on bulkhead with screened window. Also available in 54" or 60" high
- ¾" LED marker and clearance light kit meets(FMVSS108). Includes wiring harness.
- Primed and painted black, (other colors available)
- Structural channel long sills
 8'6" 14'6" 6" x 8.2 lb. channel
 16'6" 20'6" 7" x 9.8 lb. channel
 22'6" 26'6" 8" x 11.5 lb channel
- · 3" Structural cross members 12" o.c.
- 4" Formed 3/16" channel rear rail with inset stake pockets
- 10 ga. smooth steel or shiplapped KDAT pine floor
- · 10 ga. formed side rails
- 3/16" heavy-duty exterior stake pockets with 3/6" x 2" rub rail on sides
- · Standard overall width 96" (optional 102" wide)

	STANDA	RD OVER	ALL LENG	TH AND	APPROX	IMATE W	EIGHT IN	POUNDS	S*		
Length	8'6"	9'6"	10'6"	12'6"	14'6"	16'6"	18'6"	20'6"	22'6"	24'6"	26'6"
Steel Floor Weight	1161	1266	1370	1575	1782	2039	2252	2464	2751	2972	3192
Wood Floor Weight	1116	1212	1307	1496	1687	1927	2124	2319	2590	2794	2998


^{*}Length includes 3" bulkhead and rear stake pockets

OPTIONS:

- Floor: apitong hardwood, tread plate, or anti-slip floor paint
- Full rear 10" drop light apron Includes oval stop/tail, turn, reverse, and license plate lights with wiring harness
- · Cab shield (standard sizes 18", 36", 6 48")
- · ICC bumpers
- · Custom sizes and configurations available
- · Triple window in bulkhead

STAKE RACKS

- · 42" high 4 slat racks
- Constructed with 11 ga.
 reinforced hat stakes
 and 16 ga. roll formed slats
- Spring-loaded latch system on stakes assures secure attachment to body
- Optional rear swing out racks with bolt-on rear post
- Rack weight per 4' section
 4 slat 42" high, 49 lbs.




Shown with optional rear swing racks and full 10" light apron



PB9600SD Super Duty Platform / Stake Bodies

Standard Specifications & Options

- 48" high weld-on bulkhead with screened window. Also available in 54", and 60" high
- ¾" LED Marker and clearance light kit meets (FMVSS108) Includes wiring harness
- Primed and painted black (other colors available)
- Structural channel long sills
 12'6" 18'6" 7" x 9.8 lb. channel
 20'6" 26'6 " 8" x 11.5 lb. channel
- 4 " Structural channel cross members 12" o.c.
- 6" Structural channel rear and side rails
- · 7 ga. smooth steel floor
- %₆" heavy-duty exterior stake pockets with %₆" x 3" rub rail on sides and rear
- Standard overall width 96" (optional 102" wide)




^{*}Length includes 3" bulkhead and rear stake pockets with rub rail

OPTIONS:

- Floor: Shiplapped pine, apitong hardwood, tread plate, or anti-slip floor paint
- Full rear 10" drop light apron Includes oval stop/tail, turn, reverse, and license plate lights with wiring harness
- · Cab shield (standard sizes 18", 36", & 48")
- · ICC bumpers
- · Custom sizes and configurations available
- · Triple window in bulkhead

STAKE RACKS

- · 42" high 4 slat racks
- Constructed with 11 ga.
 reinforced hat stakes
 and 16 ga. roll formed slats
- Spring-loaded latch system on stakes assures secure attachment to body
- Optional rear swing out racks with bolt-on rear post
- Rack weight per 4' section
 4 slat 42" high, 49 lbs.



Shown with optional rear swing racks and full 10" light apron



CPB8400 Contractor/Platform Bodies

3 Standard Packages to Choose From
Box Delete Standard or (Cab Chassis Option) Available in All 3 Packages

Platform Only Package

Standard Specifications

- 1/2" x 3" Flat long sills, box delete
- 4" Structural channel long sills (on cab chassis option)
- 3" Formed channel 12 ga. cross members 12" o.c.
- 12 Ga. diamond plate floor with formed side rails
- 3/16" Exterior stake pockets with 1/4" x 2" tie rail on both sides
- · Fuel fill cutout in driver's side side rail
- Tapered rear corners for a nice streamlined appearance, and trailer clearance for gooseneck towing
- 41" High tapered bulkhead with screen window and center top cutout for cab rear stop light
- LED light kit includes: 6" oval S/T/T and reverse light in rear apron and bulkhead, ¾" rear and side marker and clearance lights, license plate light, and wiring harness. Meets (FMVSS108)



- Primed and painted black (other colors available)
- Universal box delete mounting kit includes; 4-Z mounting brackets with grade 8 hardware, fuel fill bracket, mud flap mounting brackets

Standard Length* and Width with Approximate Weight in Pounds						
Body Length	7'6"	8'10"	9'6"	**12'		
84" Wide Single Wheel	890	982	1025	N/A		
96" Wide Dual Wheel	959	1059	1106	1276		

^{*}Length includes bulkhead * 12' body only available in Ca6 chassis model

Cab Chassis

Specs

Same as above, except:

- 4" Structural channel long
- No fuel fill cutout (unless requested with location sp
- No mounting kit

Contractor Deluxe Package

Standard Specifications

Same as platform only, PLUS:

- · 2-Top mount steel toolboxes, black, 1 per side. Also available in aluminum
- · Bolt-on 7 ga. x 16" high rear corner posts with chain slots
- 12 Ga. x 16" high drop down tailgate with chain adjustment and spring-loaded latches
- · Filler panel between toolbox and rear post
- · Primed and painted black, (other colors available)



Shown with optio stainless steel toolbox I

Standard Toolbox Sizes with Approximate Weight* in Pounds					
Body Length	7'6"	8'10"	9'6"	12'	
Toolbox Size	72"	84"	96"	96"	
Weight, Single Wheel Width	1270	1430	1521	N/A	
Weight, Dual Wheel Width	1347	1515	1610	1843	

^{*}Weight includes body


Contractor Plus Package

Standard Specifications

Same as platform only, PLUS:

- 12 Ga. x 16" high drop down liftout sides with spring loaded latches
- · Bolt-on 7 ga. x 16" high rear corner posts with chain slots
- 12 Ga. x 16" high drop down tailgate with chain adjustment and spring loaded latches

Standard Length and Width with Approximate Weight* in Pounds					
Body Length	7'6"	8'10"	9'6"	12'	
84" Wide Single Wheel	1155	1267	1321	N/A	
96" Wide Dual Wheel	1245	1365	1422	1645	





Standard Features and Specifications

- Standard FLATBED dump body includes 38" bulkhead & LED light kit
- LED light kit, includes; 6" oval S/T/T & reverse light in rear apron and bulkhead, ¾" rear and side marker and clearance lights, license plate light, & wiring harness. Meets (FMVSS108)
- 5" × 6.7 lb. structural channel long sills
- 3" formed channel 12 gauge cross members on 12 O.C.
- 12 gauge diamond plate Floor with formed side rails
- 3/16" inset stake pockets on both sides
- 4-recessed D-rings, one in each corner of floor
- SRW Standard width 80"
- · DRW Standard width 96"
- Painted black with primer undercoat & urethane top coat (other colors available)

Standar	Standard Length and Approximate Body Weight					
Length	Width for	Approx. Wt.	**Payload Cap.			
8'10"	SRW	1376	(1) 1.4 tons			
8'10"	DRW	1456	(2) 2.7 tons			

- [1] Payload capacity is approx. and based on Ford's F350 SRW box delete truck with diesel, 4x4 and reg. cab with a 11,000 lb. GVW
- (2) Payload capacity is approx. and based on Ford's F350 DRW box delete truck with diesel, 4x4 and reg. cab with a 14,000 lb. GVW
- ** Payload capacity represents maximum allowable weight of people & cargo and is reduced by optional equipment weight.

True payload must be determined after complete upfitted truck is weighed.

- Final truck installation requirements may be chassis OEM box delete wire harness kit, backup camera kit, etc.
- Truck may also need to be reprogrammed by a dealer to accept it as a box delete finished truck
- This should not be any different than any other box delete install such as a service body

Optional Aluminum Contractor Sides Spe

- Constructed with 1/4" smooth aluminum
- · Double wall (riveted)
- 12" high fold down sides with center T-handle latch
- 12" high fold down tailgate with chain adjust and center T-handle latch
- · Bolt-on steel corner post with chain slots

Options

- Gooseneck Access Panel
- Aluminum Fold Down Side Kit

Hoist & Subframe Standard Specifications

- · 100" long universal subframe designed for box delete 56' CA chassis
- · Body long sills sit down in angle subframe for a lower overall mounting height
- · Chassis specific mounting brackets and hardware included, Ford, Dodge or GMC 2019 or newer
- Front mount telescopic cylinder with 78" stroke for a 47 degree dump angle
- · Single acting 12 volt power unit installed in between subframe angles and body long sills
- Can be installed on basically any 56" CA Box Delete chassis with slight modifications to subframe & mounting brackets

Mason / Contractor Dump Bodies

Standard Specifications & Options



Tailgate Standard Features:

- · Constructed with 10 ga. steel
- Fully boxed frame with two 12 ga. vertical posts
- · Standard height 6" higher than sides
- Fully double-acting with bottom release lever at driver's side, upper release is quick release screw pin style
- Standard with spreader chains and banjo eye chainholders on rear post

Body Standard Features:

- 6" x 8.2 lb. structural channel long sills
- 3" structural channel cross members 12 o.c.
- 10 ga. steel floor formed with inner side wall
- 12 ga. outer wall sides with box formed top and V-formed outside wall with two vertical braces
- 18" cab shield, with brackets for side boards (various heights available)
- Rear posts 6" higher than sides with brackets for side boards
- LED dump body light kit includes marker and clearance lights and 1 stop/turn/tail-light per rear corner post with wiring harness. Meets [FMVSS108]
- •Available with 12", 16", 20" or 24" sides
- · Standard width 96" outside
- Inside width 86¾"
- Primed and painted black (other colors available)

Standard Le	Standard Length and Approximate Body Weight/Cubic Yards capacity*					
Length*	9'3"	10'6"	11'3"	12'6"		
12" Sides	1765/2-3	1947/2-3	2005/3-4	2187/3-4		
16" Sides	1825/3-4	2006/3-4	2076/4-5	2235/4-5		
20" Sides	1922/4-5	2119/4-5	2193/5-6	2361/5-6		
24" Sides	2114/5-6	2323/5-6	2398/6-7	2614/6-7		

^{*}Tailgate adds 3" to overall length

OPTIONS:

- 7" x 14" tailgate metering chute
- 36" or 48" cab shield
- · Custom sizes and configurations available
- Dump Hoists Electric or PTO
- · Load tarps manual or 12V



Metering Chute







Super Duty Dump Bodies

Standard Specifications & Options

Tailgate Standard Features:

- · Constructed with 7 ga. steel
- Fully boxed frame with two 10 ga. horizontal and two 10 ga. vertical braces
- · Standard height 10" higher than sides
- Top pivot is bolt-in pin style
- Bottom has dump latch with release lever at driver's side
- Standard with spreader chains and banjo eye chain holders on rear posts



- 7" x 9.8 lb. structural channel long sills
- 4" structural channel cross members 12 o.c.
- 7 ga. steel floor
- 7 ga. side walls with boxed tubing top rail and 10 ga. vertical braces
- 18" cab shield, with brackets for side boards (various heights available)
- Rear posts 10" higher than sides with brackets for side boards



- LED dump body light kit includes marker & clearance lights and one stop/turn/taillight per rear corner post with wiring harness. Meets [FMVSS108]
- · Available with 24", 30", or 36" sides
- · Standard width 96" outside
- · Inside width 861/2"
- Primed and painted black (other colors available)

Standard Length and Approximate Body Weight/Cubic Yards capacity*					
Length	10'	11'	12'		
24" Sides	2805/5.33	2986/5.87	3179/6.40		
30" Sides	2958/6.67	3152/7.34	3350/8.00		
36" Sides	3082/8.00	3318/8.81	3528/9.61		

^{*}Tailgate adds 3" to overall length

OPTIONS:

- 123/8" x 131/2" tailgate metering chute
- · 36" or 48" cab shield
- Custom sizes
- Dump hoists electric or PTO
- · Load tarps manual or 12V
- · Spreader apron







Standard Features and Specifications

- · Standard dump body includes 38" bulkhead & led light kit
- · Light kit consist of S/T/T & reverse lights 1-per side, marker & clearance lights with rubber grommets & wiring harness
- 5'X 6.7 Lb. Structural channel long sills
- 3" Formed channel 12 ga. Crossmembers on 12 O.C.
- · 12 ga. steel floor formed with inner side wall
- 12 ga. outer wall sides with box formed top and v-formed outside wall
- Front and rear posts 6" higher than sides with side boards brackets
- · Available in 12" sides
- SRW standard width 81" outside and 71¾" inside
- DRW standard width 96" outside and 86¾" inside
- · Painted black with primer undercoat & urethane top coat (other colors available)

Standard Length and Approximate Body Weight/Cubic Yards capacity*					
Length	Width for	Side Height	Approx. Wt.	**Payload Cap.	Capacity
8'8"	SRW	12"	1650	(1) 1.3 tons	1.9 cu. ya
8'8"	DRW	12"	1750	(2) 2.5 tons	2.3 cu. yd

- [1] Payload capacity is approx. and based on Ford's F350 SRW box delete truck with diesel, 4x4 and reg. cab with a 11,000 lb. GVW
- (2) Payload capacity is approx. and based on Ford's F350 DRW box delete truck with diesel, 4x4 and reg. cab with a 14,000 lb. GVW
- ** Payload capacity represents maximum allowable weight of people & cargo and is reduced by optional equipment weight.

True payload must be determined after complete upfitted truck is weighed.

- Final truck installation requirements may be chassis DEM box delete wire harness kit, backup camera kit, etc.
- Truck may also need to be reprogrammed by a dealer to accept it as a box delete finished truck
- This should not be any different than any other box delete install such as a service body

Aluminum Tailgate Specs

- · Constructed with 3/18 ALUMINUM
- Fully boxed frame with 2 vertical braces
- · Standard height 6" higher than sides
- · Double acting with bottom release pin at reboth sides, upper release is quick-release s pin style
- · Standard with spreader chains and banjo ev chain holders on rear posts

Options

- · 12" cab shield
- · Fold down sides
- · No tarp kit

Hoist & Subframe Standard Specifications

- 100" long universal subfra designed for box delete 56' CA chassis
- · Body long sills sit down in angle subframe for a lowe overall mounting height
- Chassis specific mounting brackets and hardware included, Ford, Dodge or G 2019 and newer.
- Front mount telescopic cylinder with 78" stroke fo 47 degree dump angle
- · Single acting 12 volt power installed in between subfra angles and body long sills
- · Can be installed on basical any 56" CA Box Delete cha with slight modifications t subframe & mounting brad





LB3000 LANDSCAPE / TRASH BODIES

Standard Specifications & Options

- ¾" LED marker and clearance light kit meets (FMVSS108) Includes wiring harness
- Primed and painted black, (other colors available)
- · Standard width 951/2" outside
- 891/2" inside width
- Structural channel long sills 7" x 9.8 lb. channel
- 3" 10 ga. formed channel cross-members 12" o.c.
- · 4" channel rear rail
- 10 ga. smooth steel floor with formed side rails
- 12 ga. formed steel door with box tubing frame
- 42" or 48" high weld-on bulkhead and sides
- 10 ga. formed steel sides with box tubing top rail
- · Barn door style tailgates with dual cam latch system
- · 50" curbside door with dual cam latch system



Shown with optional cab shield


Standard Outside Length and Approximate Weight in Pounds*						
Length	9'6"	11'6"	12'6"	14'6"	16'6"	
Weight	2015	2295	2435	2737	3025	

^{*}Rear hinge and latch system adds 2½" to overall length

OPTIONS:

- Full rear 10' drop light apron, 2 oval stop/ turn/tail lights and 1 reverse light per side plus marker, clearance and license plate lights with wiring harness
- Cab shield —
 Standard sizes, 18", 36", 8 48"
- · Custom heights on sides and bulkhead
- · Custom width and length
- Dump through 24" bottom tailgate, and top barn doors (See picture)
- · Rope/Tarp Hooks on Both Sides

- Dump hoist electric or PTO
- · Load tarps, manual or 12V
- · ICC Bar



 30" high rear barn doors (Recommended for use with optional chipper top)

See separate page for Chipper Top



Optional dump tailgate and optional mesh on top doors



^{*}Inside length approximately 5½" less than outside

Appalachian Dump Bodies

Standard Specifications & Options



Aluminum Tailgate Standard Features

- Constructed with 3/18" aluminum
- Fully boxed frame with two vertical posts
- Standard height 6" higher than sides
- Fully double-acting with bottom release lever at driver's side, upper release is quick release screw pin style
- · Standard with spreader chains and banjo eye chainholders on rear post

Standard Length & Approximate Body Weight					
Length*	9'3"	11'3"			
12" Sides	1954	2207			
16" Sides	1999	2289			
20" Sides	2099	2411			

^{*}Tailgate adds 3" to overall length

OPTIONS

- Custom sizes and configurations available
- Dump hoists electric or PTO
- Load tarps manual or 12V

Body Standard Features

- 6" x 8.2 lb. structural channel long sills
- 3" structural channel cross members 12 o.c.
- 7 ga. steel floor formed with inner side wall
- 12 ga. outer wall sides with box formed top and V-formed outside wall with two vertical braces
- 36" cab shield, with brackets for side boards (various heights available)
- Rear posts 6" higher than sides with tall rear board pockets notched into rear post and 2" lower than cab shield.
- LED dump body light kit includes marker and clearance lights and 1 stop/turn/tail/reverse light per rear corner post with wiring harness. Meets (FMVSS108)
- · Available with 12", 16" or 20" sides
- · Standard width 96" outside
- · Inside width 863/4"
- Primed and painted black (other colors available)



Rear Post Profile

CB3000 CHIPPER/FORESTRY BODIES

Standard Specifications & Options

- · Body includes 66" or 72" high sides including tapered roof top with vents in side wall
- 30" high rear barn doors with dual cam latch system
- · LED light kit, includes; 6" oval S/T/T and reverse lights in rear apron and roof channel, 3/4" rear and side marker and clearance lights, & wiring harness, meets (FMVSS108)
- Structural channel long sills; 7" x 9.8 lb. channel
- 3" 10 ga. formed channel crossmembers 12' O.C.
- · 4" channel rear rail
- 10 ga, smooth steel floor with formed side rails
- 10 ga. smooth steel sides with box tubing top rail
- 14 ga. formed steel roof with tubing roof bows
- 95%" standard outside width with 89%" inside width
- · Painted white with primer undercoat & urethane top coat (other colors available)
- · Black interior rubberized chip protection coating, floor, sides & top

Cubic Yard Capacity						
Overall Outside Dimensions, length x width	Approx. weight	Cubic Yards				
96" x 9'6" x 66" high	2880	13				
96" x 12' x 66" high	3175	17				
96"'x 14' x 72" high	3492	22				
96" × 16' × 72" high	3871	25				



OTHER BODY OPTIONS

- · Front cutout for B-pack toolbox overhang, not available with 9'6" body
- · Ladder rack, bolt-on three-piece with ladder 🧢 roller on curbside
- 17" x 69" ladder with two rung flip down section, bolt on for 66" high body
- 17" x 75" Ladder with two rung flip down section, bolt on for 72" high body
- · Ladder storage compartment with shelf for pruners on curbside, with sloped top

